

beveled 2V Article number 10036526 / XYGV4KFD Bevel Moisture content 5-9% Dfl-s1 Wood Oak Number of slotted top layers Fire protection classification Grading Animoso Surface structure brushed Content of formaldehyde E 1 Product type 3-layer parquet m² per carton 2,76 **PCP** content NPD Brinell Value Format 14mm Plank Castle Boards per carton 6 38 Shrinking and swelling 14 x 209 x 2200 mm 21.5 Dimensions Weight per carton (kg) 138 Top layer thickness 3,5 mm m² per pallet **Breaking strength** Core material Spruce / Spruce Boxes per pallet 50 Thermal conductivity (W/(m*K) Connection 5G Click Weight per pallet (kg) 1075 Thermal resistance (m^{2*}K)/W 0,109 Floor heating EN 13489 USRV 45 suitable **EN Norm** Antislip performance (CE) Antislip performance (DIN) R10 Treatment Live Natural oil FSC claim controlled sources Appearance Dark floors Performance classification Class 1 Nobb.number 50710482



Density





>= 500kg/m³



EAN Code





7035580182283

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Colour

Grey Pepper