

Ash White Marcato

Product details / Technical properties

| Article number 10036653 / ASG882PD Bevel square edged Moisture content 5-9% | |
|---|-----|
| | |
| Wood Ash Number of slotted top layers 2 Fire protection classification Dfl-s1 | |
| Grading Marcato Surface structure unbrushed Content of formaldehyde E 1 | |
| Product type 3-layer parquet m ² per carton 3,04 PCP content NPD | |
| Format 14mm Plank 138 Boards per carton 10 Brinell Value 36 | |
| Dimensions 14 x 138 x 2200 mm Weight per carton (kg) 23,5 Shrinking and swelling | |
| Top layer thickness3,5 mmm² per pallet127,68Breaking strengthNPD | |
| Core material Spruce / Spruce Boxes per pallet 42 Thermal conductivity (W/(m*K) 0,125 | |
| Connection 5G Click Weight per pallet (kg) 987 Thermal resistance (m ^{2*} K)/W 0,112 | |
| Floor heating suitable EN Norm EN 13489 Antislip performance (CE) USRV 33 | |
| Treatment Live Matt lacquer white FSC claim controlled sources Antislip performance (DIN) R9 | |
| Appearance Light floors Performance classification Class 1 Nobb.number | |
| Colour White Density >= 500kg/m³ EAN Code 7035580066 | 972 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

