

10041721 / ETGL35TD Article number Oak Wood Grading Andante Product type 3-layer parquet Format 14mm Longstrip 3-Strip Dimensions 14 x 215 x 2200 mm Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Matt lacquer Appearance Golden floors

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim Performance classification

square edged 0 unbrushed 2,84 6 21 142 50 1050 EN 13489 controlled sources Class 1 >= 500kg/m<sup>3</sup>

Moisture content 5-9% Dfl-s1 Fire protection classification Content of formaldehyde E 1 **PCP** content NPD **Brinell Value** 38 Shrinking and swelling **Breaking strength** Thermal conductivity (W/(m\*K) Thermal resistance (m<sup>2\*</sup>K)/W 0,11 USRV 33 Antislip performance (CE)

Antislip performance (DIN) R9 50693644 7035580186304



Toscana



Density







Nobb.number

**EAN Code** 





Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Colour