



Oak Pale White Vivo

Product details / Technical properties

Article number	10125655 / PIGDV6FD	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Vivo	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	3,19	PCP content	NPD
Format	14mm Plank 181	Boards per carton	8	Brinell Value	38
Dimensions	14 x 181 x 2200 mm	Weight per carton (kg)	25	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	127,6	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	40	Thermal conductivity (W/(m*K))	0,13
Connection	5G Click	Weight per pallet (kg)	1000	Thermal resistance (m²*K)/W	0,11
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 91
Treatment	Live Pure lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R11
Appearance	Light floors	Performance classification	Class 1	Nobb.number	53111058
Colour	Pale White	Density	$\geq 500\text{kg/m}^3$	EAN Code	7035580209164



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.