

Article number	10135813 / BD2LSSTY	Bevel	square edged	Moisture content	5-9%
Wood	Beech	Number of slotted top layers		Fire protection classification	Dfl-s1
Grading	Sport	Surface structure	unbrushed	Content of formaldehyde	E 1
Product type	Sportsfloor	m² per carton	1,89	PCP content	NPD
Format	23mm Sport	Boards per carton	4	Brinell Value	37
Dimensions	23 x 215 x 2200 mm	Weight per carton (kg)	21	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	85,05	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	45	Thermal conductivity (W/(m*K))	
Connection	T/G	Weight per pallet (kg)	945	Thermal resistance (m²*K)/W	
Floor heating	conditionally suitable	EN Norm	EN 13489	Antislip performance (CE)	
Treatment	Squash finish	FSC claim	FSC™ Mix 70%	Antislip performance (DIN)	
Appearance	Golden floors	Performance classification	Class 1	Nobb.number	
Colour		Density	>= 500kg/m³	EAN Code	7035580211266



www.blauer-engel.de/liz176

CE
GS
Boen AS
Topdalsveien 426-428, 4658 Tveit, Norway
Parquet flooring according to EN 12489-2:2017-12 and EN 14342:2013, 9,5-23 mm total thickness, parquet for indoor use
DOP 4658, NB 0756
Dfl-s1, E1, density >= 500kg/m³, thermal conductivity <= 0,14 W/mK

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.