



Ash White Reggae

Product details / Technical properties

Article number	10035477 (ASHL82TD)	Bevel	square edged	Moisture content	5-9%
Wood	Ash	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Reggae	Surface structure	Unbrushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	2,84	PCP content	NPD
Format	Longstrip	Boards per carton	6	Brinell Value (N/mm²)	36
Dimensions	1/2 x 8-15/32 x 86-5/8 inch	Weight per carton (kg)	21	Shrinking and swelling	
Top layer thickness	2,5 mm	m² per pallet	142	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K))	
Connection	5G Click	Weight per pallet (kg)	1050	Thermal resistance (m²K)/W	
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Light	Performance classification	Class 1	Nobb.number	
Colour	White	Density	>= 500kg/m³	EAN Code	7035580184393



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.