

| Article number | 10036176 (BDBASTSY) | Bevel | square edged | Moisture content | 5-9% |
|---------------------|------------------------|------------------------------|--------------|--|---------------|
| Wood | Beech | Number of slotted top layers | 0 | Fire protection classification | Dfl-s1 |
| Grading | Sport | Surface structure | unbrushed | Content of formaldehyde | E 1 |
| Product type | Sportsfloor | m² per carton | 1,81 | PCP content | NPD |
| Format | Boflex | Boards per carton | 6 | Brinell Value (N/mm²) | 37 |
| Dimensions | 30 x 137 x 2200 mm | Weight per carton (kg) | 23,245 | Shrinking and swelling | |
| Top layer thickness | 5,5 mm | m² per pallet | 88,69 | Breaking strength | NPD |
| Core material | Spruce / Spruce | Boxes per pallet | 49 | Thermal conductivity (W/(m*K) | |
| Connection | T/G | Weight per pallet (kg) | 11395 | Thermal resistance (m ² *K)/W | |
| Floor heating | conditionally suitable | EN Norm | EN 13489 | Antislip performance (CE) | |
| Treatment | T79 Sport lacquer | FSC claim | FSC™ Mix 70% | Antislip performance (DIN) | |
| Appearance | Golden floors | Biological durability | Class 1 | Nobb.number | 53111058 |
| Colour | Transparent | Density | >= 500kg/m³ | EAN Code | 7035580180227 |














Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

