

Oak White Andante Live Pure

Article number 10036252 (EBGV36FD) Wood Oak Grading Andante Product type 3-layer parquet 14mm Plank Castle Format 14 x 209 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce 5G Click Connection Floor heating suitable Treatment Live Pure lacquer Appearance Light floors Colour White

> INSTITUT TESTED PRODUCT ID 0921 - 33879 - 003

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) **EN Norm** FSC claim Performance classification Density

beveled 2V 1 brushed 2,76 6 21.5 138 50 1075 EN 13489 Class 1 >= 500kg/m³

controlled sources







	CE		
	06		
Boen AS			
	Topdalsveien 406-408, 4658 Tveit, Norway		
Parquet flooring according EN 13489: 2017-12 and EN 14342 9,5-23 mm total thickness; parquet for indoor use			
	DOP 4658; NB 0766		
	DR-sl; EL density >= 500kg/m ^s thermal conductivity >= 0.14 W/mK		

Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

CERTIFIED BY



Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m ^{2*} K)/W	0,109
Antislip performance (CE)	USRV 91
Antislip performance (DIN)	R11
Nobb.number	49254145
EAN Code	7035580174073