

Oak Vivo

Article number	10036295 (EIGVVKFD)	Be
Wood	Oak	
Grading	Vivo	
Product type	3-layer parquet	
Format	14mm Plank Castle	Во
Dimensions	14 x 209 x 2200 mm	We
Top layer thickness	3,5 mm	m
Core material	Spruce / Spruce	Во
Connection	5G Click	We
Floor heating	suitable	EN
Treatment	Live Natural oil	FS
Appearance	Golden floors	Pe
Colour		De

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classification
Density

1
unbrushed
2,76
6
21,5
138
50
1075
EN 13489
controlled sources
Class 1

>= 500kg/m³

beveled 2V

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m²*K)/W	0,109
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	49254005
EAN Code	7035580086819
	Fire protection classification Content of formaldehyde PCP content Brinell Value (N/mm²) Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W Antislip performance (CE) Antislip performance (DIN) Nobb.number



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

