

Article number	10036302 (EIGVV5FD)	
Wood	Oak	
Grading	Vivo	
Product type	3-layer parquet	
Format	14mm Plank Castle	
Dimensions	14 x 209 x 2200 mm	
Top layer thickness	3.5 mm	
Core material	Spruce / Spruce	
Connection	5G Click	
Floor heating	suitable	
Treatment	Live Matt lacquer	
Appearance	Golden floors	
Colour	Transparent	

Bevel
Number of slotted top laye
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classification
Deneity

beveled	d 2V
1	
sanded	
2.76	
6	
21.5	
138	
50	
1075	
EN 1348	9
controlle	ed sources
Class 1	
>= 500kg	g/m³

Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0.129
Thermal resistance (m ² *K)/W	0.109
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	43657066
	Fire protection classification Content of formaldehyde PCP content Brinell Value (N/mm²) Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W Antislip performance (CE) Antislip performance (DIN)











EAN Code





7035580048121

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

