

Article number 10036418 (OHGVVKFD) Bevel		beveled 2V	Moisture content	5-9%
Wood Oak Number	of slotted top layers	1	Fire protection classification	Dfl-s1
Grading Vivo Surface	structure	brushed	Content of formaldehyde	E 1
Product type 3-layer parquet m² per co	arton	2,76	PCP content	NPD
Format 14mm Plank Castle Boards p	oer carton	6	Brinell Value (N/mm²)	38
Dimensions 14 x 209 x 2200 mm Weight p	oer carton (kg)	21,8	Shrinking and swelling	
Top layer thickness 3,5 mm m² per pe	allet	138	Breaking strength	NPD
Core material Spruce / Spruce Boxes pe	er pallet	50	Thermal conductivity (W/(m*K)	0,129
Connection 5G Click Weight p	oer pallet (kg)	1090	Thermal resistance (m <sup>2*</sup> K)/W	0,109
Floor heating suitable EN Norm	ı	EN 13489	Antislip performance (CE)	USRV 45
Treatment Live Natural oil FSC claim	m	controlled sources	Antislip performance (DIN)	R10
Appearance Golden floors Performa	ance classification	Class 1	Nobb.number	50710516
Colour Honey Density		>= 500kg/m³	EAN Code	7035580182306













Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

