

Article number	10036525 (XH4V4MFD)	
Wood	Oak	Nu
Grading	Country	Sur
Product type	3-Layer	m²
Format	Castle plank	Вос
Dimensions	9/16 x 8-1/4 x 86-5/8 inch	
Top layer thickness	3,5 mm	m²
Core material	Spruce / Spruce	Вох
Connection	T/G	We
Floor heating	suitable	EN

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classification
Density

beveled 2V
1
Unbrushed
2,76
6
21,5
138
50
1075
EN 13489
controlled sources
Class 1
>= 500kg/m <sup>3</sup>

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m <sup>2*</sup> K)/W	0,109
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	
EAN Code	7035580086260















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.



Treatment

Colour

**Appearance**