

| Article number | 10036536 (EACXVKFD) | Bevel | beveled 4V | Moisture content | 5-9% |
|---------------------|--------------------------------|------------------------------|--------------------|--|---------------|
| Wood | Oak | Number of slotted top layers | 0 | Fire protection classification | Dfl-s1 |
| Grading | Canyon | Surface structure | sanded | Content of formaldehyde | E 1 |
| Product type | 3-layer parquet | m² per carton | | PCP content | NPD |
| Format | 20mm Plank Chalet | Boards per carton | | Brinell Value (N/mm²) | 38 |
| Dimensions | 20 x 200-395 x 2000-4000 mm | Weight per carton (kg) | 11.152 | Shrinking and swelling | |
| Top layer thickness | 4.5 mm | m² per pallet | 0 | Breaking strength | NPD |
| Core material | Spruce / Spruce | Boxes per pallet | | Thermal conductivity (W/(m*K) | 0.128 |
| Connection | T/G | Weight per pallet (kg) | 0 | Thermal resistance (m ^{2*} K)/W | 0.156 |
| Floor heating | suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 59 |
| Treatment | Live Natural oil | FSC claim | controlled sources | Antislip performance (DIN) | R10 |
| Appearance | Brown floors | Performance classification | Class 1 | Nobb.number | 49327861 |
| Colour | Antique | Density | >= 500kg/m³ | EAN Code | 7035580175919 |













Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

