

Oak White

Product details / Technical properties

Article number	10036554	**Bevel**	beveled 4V	**Moisture content**	5-9%
Wood	Oak	**Number of slotted top layers**	0	**Fire classification (floating)**	
Grading	Traditional	**Surface structure**	sanded	**Fire classification (glued)**	Cfl-s1
Product type	3-layer parquet	**m² per carton**		**Content of formaldehyde**	E 1
Format	Chalet	**Boards per carton**		**PCP content**	NPD
Dimensions	20 x 200-395 x 2000-4000 mm	**Weight per carton (kg)**	13.65	**Brinell Value (N/mm²)**	38
Top layer thickness	4.5 mm	**m² per pallet**	0	**Breaking strength**	NPD
Core material	Spruce / Spruce	**Boxes per pallet**		**Thermal conductivity (W/(m*K)**	0.128
Connection	T/G	**Weight per pallet (kg)**	0.0	**Thermal resistance (m²*K)/W**	0.156
Floor heating	suitable	**EN Norm**	EN 13489	**Antislip performance (CE)**	USRV 59
Treatment	Live Natural	**Wood origin**	controlled sources	**Antislip performance (DIN)**	R10
Appearance	light	**Performance classification**	Class 1	**Nobb.number**	46308583
Colour	White	**Density**	>= 500kg/m³	**EAN Code**	7035580137030

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.