

Article number	10036555 (EICX4UFD)	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Traditional	Surface structure	sanded	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton		PCP content	NPD
Format	20mm Plank Chalet	Boards per carton		Brinell Value (N/mm²)	38
Dimensions	20 x 200-395 x 2000-4000 mm	Weight per carton (kg)	11,152	Shrinking and swelling	
Top layer thickness	4,5 mm	m² per pallet	0	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet		Thermal conductivity (W/(m*K)	0,128
Connection	T/G	Weight per pallet (kg)	0	Thermal resistance (m <sup>2*</sup> K)/W	0,156
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	
Treatment	unfinished	FSC claim	controlled sources	Antislip performance (DIN)	
Appearance		Performance classification	Class 1	Nobb.number	53111058
Colour		Density	>= 500kg/m³	EAN Code	7035580117810














Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

