



## Oak Transparent Vivo

### Product details / Technical properties

|                            |                     |                                     |                         |  |               |
|----------------------------|---------------------|-------------------------------------|-------------------------|--|---------------|
| <b>Article number</b>      | 10036677 (EBG8VKFD) | <b>Bevel</b>                        | beveled 2V              | <b>Moisture content</b>                      | 5-9%          |
| <b>Wood</b>                | Oak                 | <b>Number of slotted top layers</b> | 2                       | <b>Fire protection classification</b>        | Dfl-s1        |
| <b>Grading</b>             | Vivo                | <b>Surface structure</b>            | brushed                 | <b>Content of formaldehyde</b>               | E 1           |
| <b>Product type</b>        | 3-layer parquet     | <b>m<sup>2</sup> per carton</b>     | 3.04                    | <b>PCP content</b>                           | NPD           |
| <b>Format</b>              | 14mm Plank 138      | <b>Boards per carton</b>            | 10                      | <b>Brinell Value (N/mm<sup>2</sup>)</b>      | 38            |
| <b>Dimensions</b>          | 14 x 138 x 2200 mm  | <b>Weight per carton (kg)</b>       | 25.5                    | <b>Shrinking and swelling</b>                |               |
| <b>Top layer thickness</b> | 3.5 mm              | <b>m<sup>2</sup> per pallet</b>     | 127.68                  | <b>Breaking strength</b>                     | NPD           |
| <b>Core material</b>       | Spruce / Spruce     | <b>Boxes per pallet</b>             | 42                      | <b>Thermal conductivity (W/(m*K))</b>        | 0.129         |
| <b>Connection</b>          | 5G Click            | <b>Weight per pallet (kg)</b>       | 1071                    | <b>Thermal resistance (m<sup>2</sup>K)/W</b> | 0.109         |
| <b>Floor heating</b>       | suitable            | <b>EN Norm</b>                      | EN 13489                | <b>Antislip performance (CE)</b>             | USRV 45       |
| <b>Treatment</b>           | Live Natural oil    | <b>FSC claim</b>                    | controlled sources      | <b>Antislip performance (DIN)</b>            | R10           |
| <b>Appearance</b>          | Golden floors       | <b>Performance classification</b>   | Class 1                 | <b>Nobb.number</b>                           | 49253222      |
| <b>Colour</b>              | Transparent         | <b>Density</b>                      | >= 500kg/m <sup>3</sup> | <b>EAN Code</b>                              | 7035580085966 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.