



Maple Can. Transparent Andante

Product details / Technical properties

Article number	10037077 (MAG835PD)	Bevel	square edged	Moisture content	5-9%
Wood	Maple Can.	Number of slotted top layers	2	Fire protection classification	Dfl-s1
Grading	Andante	Surface structure	Unbrushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	3,04	PCP content	NPD
Format	5-1/2" plank	Boards per carton	10	Brinell Value (N/mm²)	40
Dimensions	9/16 x 5-7/16 x 86-5/8 inch	Weight per carton (kg)	24,2	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	127,68	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	42	Thermal conductivity (W/(m*K))	0,125
Connection	5G Click	Weight per pallet (kg)	1016,4	Thermal resistance (m²*K)/W	0,112
Floor heating	conditionally suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Light	Performance classification	Class 1	Nobb.number	43667453
Colour	Transparent	Density	>= 500kg/m ³	EAN Code	7035580046103



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.