

Maple Can. Transparent Andante

Product details / Technical properties

Article number	10037077 (MAG835PD)	
Wood	Maple Can.	
Grading	Andante	
Product type	3-layer parquet	
Format	14mm Plank 138	
Dimensions	14 x 138 x 2200 mm	
Top layer thickness	3,5 mm	
Core material	Spruce / Spruce	
Connection	5G Click	
Floor heating	conditionally suitable	
Treatment	Live Matt lacquer	
Appearance	Light floors	
Colour	Transparent	

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classification
Density

1	
	without bevel
	2
	unbrushed
	3,04
	10
	24,2
	127,68
	42
	1016,4
	EN 13489
	controlled sources
	Class 1
	>= 500kg/m³

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	40
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,125
Thermal resistance (m ^{2*} K)/W	0,112
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	43667453
EAN Code	7035580046103



06 Boon A5 Topotatriem - K20-400, 400 Treet, Nor-1176 EN 1349 2017-20 and 19 14-324 potaget floating opcording to PA 1349 2017-20 and 19 14-324 potaget for motion-use potaget for motion-use D0 4-545, 80 core D1-81, 61, estanty - 503-pm² Bernal conductivity - 0.14 W/m

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

