

| Article number | 10037123 (NUG83KPD) | Bevel | square edged | Moisture content | 5-9% |
|---------------------|-----------------------------|------------------------------|--------------------|--|---------------|
| Wood | Walnut Am. | Number of slotted top layers | 2 | Fire protection classification | Dfl-s1 |
| Grading | Andante | Surface structure | sanded | Content of formaldehyde | E1 |
| Product type | 3-Layer | m² per carton | 3,04 | PCP content | NPD |
| Format | 5-1/2" plank | Boards per carton | 10 | Brinell Value (N/mm²) | 34 |
| Dimensions | 9/16 x 5-7/16 x 86-5/8 inch | Weight per carton (kg) | 23,5 | Shrinking and swelling | |
| Top layer thickness | 3,5 mm | m² per pallet | 127,68 | Breaking strength | NPD |
| Core material | Spruce / Spruce | Boxes per pallet | 42 | Thermal conductivity (W/(m*K) | 0,131 |
| Connection | 5G Click | Weight per pallet (kg) | 987 | Thermal resistance (m ² *K)/W | 0,107 |
| Floor heating | suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 59 |
| Treatment | Live Natural oil | FSC claim | controlled sources | Antislip performance (DIN) | R10 |
| Appearance | Brown | Performance classification | Class 1 | Nobb.number | 49426194 |
| Colour | Transparent | Density | >= 500kg/m³ | EAN Code | 7035580083566 |
















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

