

## Walnut am. Transparent Andante

10037133 (NUG835PD) Article number Walnut am. Wood Grading Andante Product type 3-layer parquet 14mm Plank 138 Format 14 x 138 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Matt lacquer Appearance Brown floors Colour Transparent

Bevel
Number of slotted top lay
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	without bevel
top layers	2
	sanded
	3,04
	10
(kg)	23,5
	127,68
	42
kg)	987
	EN 13489
	controlled sources

Class 1

>= 500kg/m<sup>3</sup>



Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	34
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,131
Thermal resistance (m <sup>2</sup> *K)/W	0,107
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	43667483
EAN Code	7035580046530
	Fire protection classification Content of formaldehyde PCP content Brinell Value (N/mm²) Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W Antislip performance (CE) Antislip performance (DIN) Nobb.number

REAL







Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

