

Oak Coral Animoso

10037186 (OPG84MFD) Article number Oak Wood Grading Animoso Product type 3-layer parquet 14mm Plank 138 Format 14 x 138 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Natural oil Appearance Light floors Colour Coral

Bevel
Number of slotted top laye
Surface structure
m ² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classification
Density

INSTITUT

TESTED PRODUCT

ID 0921 - 33879 - 003

	beveled 2V
ayers	2
	sanded
	3,04
	10
	23,5
	127,68
	42
	987
	EN 13489
	controlled source
ition	Class 1
	>= 500kg/m³









Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

CON CERTIFIED BY



Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m ^{2*} K)/W	0,109
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	45964758
EAN Code	7035580080718