

Article number 10037272 (EBGDV5FD) Wood Oak Grading Vivo Product type 3-layer parquet 14mm Plank 181 Format 14 x 181 x 2200 mm Dimensions Top layer thickness 3.5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable

Appearance Golden floors Colour Transparent

Treatment

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim

8 25 127.6 40 1000 EN 13489 Performance classification Class 1 Density >= 500kg/m³

beveled 2V brushed 3.19 controlled sources

Moisture content Fire protection classification Content of formaldehyde **PCP** content Brinell Value (N/mm²) Shrinking and swelling **Breaking strength** Thermal conductivity (W/(m*K) Thermal resistance (m^{2*}K)/W Antislip performance (CE)

Antislip performance (DIN) Nobb.number

EAN Code



5-9% Cfl-s1

E 1

NPD

38

0.11

R9

USRV 48

7035580155607



Live Matt lacquer











Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

