

## Oak Transparent Andante

10037275 (EBGD3KFD) Article number Wood Oak Grading Andante Product type 3-layer parquet 14mm Plank 181 Format 14 x 181 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Live Natural oil Treatment Appearance Golden floors Colour Transparent

Bevel
Number of slotted top laye
Surface structure
m <sup>2</sup> per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

INSTITUT TESTED PRODUCT ID 0921 - 33879 - 003

	beveled 2V
slotted top layers	1
ucture	brushed
on	3,19
carton	8
carton (kg)	25
et	127,6
pallet	40
pallet (kg)	1000
	EN 13489
	controlled sc
durability	Class 1
	$>= 500 \text{kg/m}^3$

	1110	
rushed	Cor	
19	PCF	
	Brin	
5	Shri	
27,6	Bre	
)	The	
000	The	
13489	Ant	
ontrolled sources	Ant	
lass 1	Nol	
= 500kg/m³		

C CERTIFIED BY SCS Global Service





	CE	
	06	
Boen AS		
Topd	alsveien 406-408, 4658 Tveit, Norway	
	Parquet flooring according to 13489: 2017-12 and EN 14342:2013 9.5-23 mm total thickness: parquet for indoor use	
	DOP 4658; NB 0766	
	Dfl-sl; El, density >= 500kg/m <sup>s</sup> ermal conductivity >= 0.14 W/mK	

Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

/uz176



## Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m²*K)/W	0,11
Antislip performance (CE)	USRV 45
Antislip performance (DIN)	R10
Nobb.number	53111058
EAN Code	7035580150602