



Oak White Animoso

Product details / Technical properties

Article number	10037292 (EBGD4MFD)	Bevel	beveled 2V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	1	Fire protection classification	Dfl-s1
Grading	Animoso	Surface structure	brushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	3.19	PCP content	NPD
Format	14mm Plank 181	Boards per carton	8	Brinell Value (N/mm²)	38
Dimensions	14 x 181 x 2200 mm	Weight per carton (kg)	23	Shrinking and swelling	
Top layer thickness	3.5 mm	m² per pallet	127.6	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	40	Thermal conductivity (W/(m*K))	0.13
Connection	5G@ Click	Weight per pallet (kg)	920	Thermal resistance (m²*K)/W	0.11
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 45
Treatment	Live Natural oil	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Light floors	Performance classification	Class 1	Nobb.number	53111058
Colour	White	Density	>= 500kg/m ³	EAN Code	7035580150572



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.