

1

sanded

3,19

8

25

40

1000

EN 13489

Class 1

>= 500kg/m³

controlled sources

127,6

Oak Transparent Vivo

Article number 10037328 (EIGDV5FD) Wood Oak Grading Vivo Product type 3-layer parquet 14mm Plank 181 Format 14 x 181 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Matt lacquer Appearance Golden floors Colour Transparent

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

beveled 2V Moisture content Fire protection classification Content of formaldehyde PCP content

E 1 NPD Brinell Value (N/mm²) 38 Shrinking and swelling Breaking strength NPD Thermal conductivity (W/(m*K) 0,13 Thermal resistance (m^{2*}K)/W 0,11 USRV 33 Antislip performance (CE) Antislip performance (DIN) R9 Nobb.number 53111058 EAN Code 7035580091721

Product details / Technical properties

5-9% Cfl-s1



Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

