

Article number	10037328 (EIGDV5FD)	
Wood	Oak	
Grading	Vivo	
Product type	3-layer parquet	
Format	14mm Plank 181	
Dimensions	14 x 181 x 2200 mm	
Top layer thickness	3,5 mm	
Core material	Spruce / Spruce	
Connection	5G Click	
Floor heating	suitable	
Treatment	Live Matt lacquer	
Appearance	Golden floors	
Colour	Transparent	

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	beveled 2V
ayers	1
	unbrushed
	3,19
	8
	25
	127,6
	40
	1000
	EN 13489
	controlled sources
	Class 1
	>= 500kg/m³

Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m <sup>2*</sup> K)/W	0,11
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	53111058
EAN Code	7035580091721














Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

