

Article number	10041645 (BDGL35TD)	Bevel	without bevel	Moisture content	5-9%
Wood	Beech	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Andante	Surface structure	unbrushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	2.84	PCP content	NPD
Format	14mm Longstrip 3-Strip	Boards per carton	6	Brinell Value (N/mm²)	37
Dimensions	14 x 215 x 2200 mm	Weight per carton (kg)	21	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	142	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K)	0.13
Connection	5G Click	Weight per pallet (kg)	1050	Thermal resistance (m <sup>2</sup> *K)/W	0.11
Floor heating	conditionally suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Golden floors	Performance classification	Class 1	Nobb.number	50693402
Colour	Transparent	Density	>= 500kg/m³	EAN Code	7035580185284















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

