

Wood Oak Number of slotted top layers 0 Fire protection classification Dfl-s1	
Grading Adagio Surface structure unbrushed Content of formaldehyde E 1	
Product type 3-layer parquet m² per carton 2,84 PCP content NPD	
Format 14mm Longstrip 3-Strip Boards per carton 6 Brinell Value (N/mm²) 38	
Dimensions 14 x 215 x 2200 mm Weight per carton (kg) 21 Shrinking and swelling	
Top layer thickness 3,5 mm m² per pallet 142 Breaking strength NPD	
Core material Spruce / Spruce Boxes per pallet 50 Thermal conductivity (W/(m*K) 0,13	
Connection 5G Click Weight per pallet (kg) 1050 Thermal resistance (m ^{2*} K)/W 0,11	
Floor heating suitable EN Norm EN 13489 Antislip performance (CE) USRV 33	
Treatment Live Matt lacquer FSC claim controlled sources Antislip performance (DIN) R9	
AppearanceGolden floorsBiological durabilityClass 1Nobb.number50693421	
ColourTransparentDensity>= 500kg/m³EAN Code7035580185925	















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

