




## Oak Transparent Finale

### Product details / Technical properties

|                            |                        |                                     |                    |                                       |               |
|----------------------------|------------------------|-------------------------------------|--------------------|---------------------------------------|---------------|
| <b>Article number</b>      | 10041794 (EIGLTPD)     | <b>Bevel</b>                        | without bevel      | <b>Moisture content</b>               | 5-9%          |
| <b>Wood</b>                | Oak                    | <b>Number of slotted top layers</b> | 0                  | <b>Fire protection classification</b> | Dfl-s1        |
| <b>Grading</b>             | Finale                 | <b>Surface structure</b>            | sanded             | <b>Content of formaldehyde</b>        | E 1           |
| <b>Product type</b>        | 3-layer parquet        | <b>m² per carton</b>                | 2,84               | <b>PCP content</b>                    | NPD           |
| <b>Format</b>              | 14mm Longstrip 3-Strip | <b>Boards per carton</b>            | 6                  | <b>Brinell Value (N/mm²)</b>          | 38            |
| <b>Dimensions</b>          | 14 x 215 x 2200 mm     | <b>Weight per carton (kg)</b>       | 21                 | <b>Shrinking and swelling</b>         |               |
| <b>Top layer thickness</b> | 3,5 mm                 | <b>m² per pallet</b>                | 142                | <b>Breaking strength</b>              | NPD           |
| <b>Core material</b>       | Spruce / Spruce        | <b>Boxes per pallet</b>             | 50                 | <b>Thermal conductivity (W/(m*K))</b> | 0,13          |
| <b>Connection</b>          | 5G Click               | <b>Weight per pallet (kg)</b>       | 1050               | <b>Thermal resistance (m²*K)/W</b>    | 0,11          |
| <b>Floor heating</b>       | suitable               | <b>EN Norm</b>                      | EN 13489           | <b>Antislip performance (CE)</b>      | USRV 31       |
| <b>Treatment</b>           | Live Satin lacquer     | <b>FSC claim</b>                    | controlled sources | <b>Antislip performance (DIN)</b>     |               |
| <b>Appearance</b>          | Golden floors          | <b>Performance classification</b>   | Class 1            | <b>Nobb.number</b>                    | 53111058      |
| <b>Colour</b>              | Transparent            | <b>Density</b>                      | >= 500kg/m³        | <b>EAN Code</b>                       | 7035580183952 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.