

Oak Transparent Sport

Product details / Technical properties

Article number	10041900 (EIALSTTY)	Bevel	square edged	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Sport	Surface structure	Unbrushed	Content of formaldehyde	E1
Product type	Sportsfloor	m² per carton	1,89	PCP content	NPD
Format	Actiflex	Boards per carton	4	Brinell Value (N/mm²)	38
Dimensions	13/16 x 8-15/32 x 86-5/8 inch	Weight per carton (kg)	20,05	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	68,04	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	36	Thermal conductivity (W/(m*K)	
Connection	5G Click	Weight per pallet (kg)	721,8	Thermal resistance (m ² *K)/W	
Floor heating	conditionally suitable	EN Norm	EN 13489	Antislip performance (CE)	
Treatment	T79 Sport lacquer	FSC claim	FSC™ Mix 70%	Antislip performance (DIN)	
Appearance	Golden	Performance classification	Class 1	Nobb.number	50766603
Colour	Transparent	Density	>= 500kg/m³	EAN Code	7035580185116



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

