

## Oak Oregon Concerto

Article number 10041987 (EYG875PD) Oak Wood Grading Concerto Product type 3-layer parquet 14mm Plank 138 Format 14 x 138 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Matt lacquer Appearance Dark floors Colour Oregon

Bevel
Number of slotted top la
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	without bevel	
f slotted top layers	2	
ructure	unbrushed	
rton	3,04	
er carton	10	
er carton (kg)	21,7	
llet	127,68	
pallet	42	
er pallet (kg)	911,4	
	EN 13489	
	controlled sources	
l durability	Class 1	

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m <sup>2*</sup> K)/W	0,109
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	53111058
EAN Code	7035580186953



>= 500kg/m³

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

