

Article number	10041988 (EQG875PD)	Bevel	square edged	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	2	Fire protection classification	Cfl-s1
Grading	Concerto	Surface structure	Unbrushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	3,04	PCP content	NPD
Format	5-1/2" plank	Boards per carton	10	Brinell Value (N/mm²)	38
Dimensions	9/16 x 5-7/16 x 86-5/8 inch	Weight per carton (kg)	23,3	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	127,68	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	42	Thermal conductivity (W/(m*K)	0,129
Connection	5G Click	Weight per pallet (kg)	978,6	Thermal resistance (m ² *K)/W	0,109
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Grey	Performance classification	Class 1	Nobb.number	53089555
Colour	Arizona	Density	>= 500kg/m³	EAN Code	7035580187578

















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

