

Oak White Vivo

Article number 10042201 (EIGVV2FD) Oak Wood Grading Vivo Product type 3-layer parquet 14mm Plank Castle Format 14 x 209 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Matt lacquer Appearance Light floors Colour White

Bevel			
Number of slotted top layers			
Surface structure			
m² per carton			
Boards per carton			
Weight per carton (kg)			
m² per pallet			
Boxes per pallet			
Weight per pallet (kg)			
EN Norm			
FSC claim			
Biological durability			
Density			

beveled 2V
1
sanded
2,76
6
21,5
138
50
1075
EN 13489
controlled sources



Moisture content	5-9%
Fire protection classification	Cfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m ^{2*} K)/W	0,109
Antislip performance (CE)	USRV 33
Antislip performance (DIN)	R9
Nobb.number	56759500
EAN Code	7035580191056



Class 1

>= 500kg/m³

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

