

10109226 (GBGVZKFD) Article number Oak Wood Grading Espressivo Product type 3-layer parquet 14mm Plank Castle Format Dimensions 14 x 209 x 2200 mm Top layer thickness 3,5 mm Core material Spruce / Spruce

Connection 5G Click Floor heating suitable Treatment Live Natural oil Appearance Golden floors Colour Transparent

Bevel
Number of slotted top layers
Surface structure
n² per carton
Boards per carton
Veight per carton (kg)
n² per pallet
Boxes per pallet
Veight per pallet (kg)
N Norm

FSC claim С **Biological durability** Density >= 500kg/m³

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m <sup>2</sup> *K)/W	0,109
Antislip performance (CE)	USRV 45
Antislip performance (DIN)	R10
Nobb.number	52000635
EAN Code	7035580197980
	Fire protection classification Content of formaldehyde PCP content Brinell Value (N/mm²) Shrinking and swelling Breaking strength Thermal conductivity (W/(m*K) Thermal resistance (m²*K)/W Antislip performance (CE) Antislip performance (DIN) Nobb.number













Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

