

Article number 10109308 (GBGDZKFD) Wood Oak Grading Espressivo Product type 3-layer parquet 14mm Plank 181 Format 14 x 181 x 2200 mm Dimensions Top layer thickness 3,5 mm

Connection 5G Click Floor heating suitable Live Natural oil Treatment Appearance Golden floors Colour Transparent

Core material

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Spruce / Spruce Boxes per pallet Weight per pallet (kg) EN Norm FSC claim

beveled 2V brushed 3,19 8 25 127,6 40 1000 EN 13489 controlled sources Performance classification Class 1 >= 500kg/m³

Moisture content 5-9% Dfl-s1 Fire protection classification Content of formaldehyde E 1 **PCP** content NPD Brinell Value (N/mm²) 38 Shrinking and swelling **Breaking strength** Thermal conductivity (W/(m\*K) 0,129 Thermal resistance (m<sup>2\*</sup>K)/W 0,109 USRV 45 Antislip performance (CE) Antislip performance (DIN) R10

Nobb.number 53111058 **EAN Code** 7035580198000



Density











Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

