

Article number	10114863 (XZCYVKFD)	Bevel	beveled 4V	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Canyon	Surface structure	Brushed	Content of formaldehyde	E1
Product type	3-Layer	m² per carton	1,65	PCP content	NPD
Format	Chaletino	Boards per carton	2	Brinell Value (N/mm²)	38
Dimensions	3/4 x 11-13/16 x 108-1/4 inch	Weight per carton (kg)	18,5	Shrinking and swelling	
Top layer thickness	4,5 mm	m² per pallet	49,5	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	30	Thermal conductivity (W/(m*K)	0,128
Connection	T/G	Weight per pallet (kg)	555	Thermal resistance (m ² *K)/W	0,156
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 45
Treatment	Live Natural oil	FSC claim	controlled sources	Antislip performance (DIN)	R10
Appearance	Dark	Performance classification	Class 1	Nobb.number	52000843
Colour	Brown Jasper	Density	>= 500kg/m³	EAN Code	7035580200543

















Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

