

## Oak Transparent Nature

Article number 10117107 (EB4V33FD) Oak Wood Grading Nature Product type 3-layer parquet 14mm Plank Castle Format 14 x 209 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection T/G Floor heating suitable Treatment Live Pure lacquer Appearance Golden floors Colour Transparent

## Bevel Number of slotted top layer Surface structure m<sup>2</sup> per carton Boards per carton Weight per carton (kg) m<sup>2</sup> per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim Biological durability Density

|        | beveled 2V         |
|--------|--------------------|
| layers | 1                  |
|        | brushed            |
|        | 2,76               |
|        | 6                  |
| 3)     | 21                 |
|        | 138                |
|        | 50                 |
| )      | 1050               |
|        | EN 13489           |
|        | controlled sources |
|        | Class 1            |

| Product details / Tec | hnical properties |
|-----------------------|-------------------|
|-----------------------|-------------------|

| Moisture content               | 5-9%          |
|--------------------------------|---------------|
| Fire protection classification | Dfl-s1        |
| Content of formaldehyde        | E 1           |
| PCP content                    | NPD           |
| Brinell Value (N/mm²)          | 38            |
| Shrinking and swelling         |               |
| Breaking strength              | NPD           |
| Thermal conductivity (W/(m*K)  | 0,129         |
| Thermal resistance (m²*K)/W    | 0,109         |
| Antislip performance (CE)      | USRV 91       |
| Antislip performance (DIN)     | R11           |
| Nobb.number                    |               |
| EAN Code                       | 7035580202950 |



>= 500kg/m³

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

