

Oak White Concerto Live Pure

10117155 (EBGL76TD) Article number Oak Wood Grading Concerto Product type 3-layer parquet Format 14mm Longstrip 3-Strip 14 x 215 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Pure lacquer Appearance Light floors Colour White

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim Performance classification Density

0
brushed
2,84
6
21
142
50
1050
EN 13489
controlled sources
Class 1

without bevel

Product	defails,	lechnical	properfies

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,13
Thermal resistance (m²*K)/W	0,11
Antislip performance (CE)	USRV 91
Antislip performance (DIN)	R11
Nobb.number	52000272
EAN Code	7035580200505



>= 500kg/m³

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

