

Oak Pale White Vivo

10118937 (PIG8V6FD) Article number Oak Wood Grading Vivo Product type 3-layer parquet 14mm Plank 138 Format 14 x 138 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Pure lacquer Appearance Light floors Colour Pale White

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classification
Density

ers	2
	brushed
	3,04
	10
	23,5
	127,68
	42
	987
	EN 13489
	controlled sources
ı	Class 1

>= 500kg/m³

beveled 2V

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m²*K)/W	0,109
Antislip performance (CE)	USRV 91
Antislip performance (DIN)	R11
Nobb.number	53516218
EAN Code	7035580204305



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

