

## Oak Transparent Vivo

10119061 (EBG8V3FD) Article number Oak Wood Grading Vivo Product type 3-layer parquet 14mm Plank 138 Format Dimensions 14 x 138 x 2200 mm Top layer thickness 3,5 mm Core material Spruce / Spruce Connection 5G Click Floor heating suitable Treatment Live Pure lacquer Appearance Golden floors Colour Transparent

Bevel
Number of slotted top laye
Surface structure
m <sup>2</sup> per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

	beveled 2V
ers	2
	brushed
	3,04
	10
	23,5
	127,68
	42
	987
	EN 13489
	controlled sources
	Class 1

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m <sup>2*</sup> K)/W	0,109
Antislip performance (CE)	USRV 91
Antislip performance (DIN)	R11
Nobb.number	53089566
EAN Code	7035580203186



>= 500kg/m<sup>3</sup>

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

