

Article number	10119061 (EBG8V3FD)	
Wood	Oak	
Grading	Vivo	
Product type	3-layer parquet	
Format	14mm Plank 138	
Dimensions	14 x 138 x 2200 mm	
Top layer thickness	3,5 mm	
Core material	Spruce / Spruce	
Connection	5G Click	
Floor heating	suitable	
Treatment	Live Pure lacquer	
Appearance	Golden floors	
Colour	Transparent	

Bevel
Number of slotted top laye
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Performance classificatio
Density

beveled 2V
2
brushed
3,04
10
23,5
127,68
42
987
EN 13489
controlled sources
Class 1
>= 500kg/m³

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m ^{2*} K)/W	0,109
Antislip performance (CE)	USRV 91
Antislip performance (DIN)	R11
Nobb.number	53089566











EAN Code





7035580203186

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

