



Walnut Am. Transparent Select

Product details / Technical properties

| | | | | | |
|----------------------------|----------------------------|-------------------------------------|-------------------------|--|---------------|
| Article number | 10123258 (NS4723FD) | Bevel | beveled 2V | Moisture content | 5-9% |
| Wood | Walnut Am. | Number of slotted top layers | 2 | Fire protection classification | Dfl-s1 |
| Grading | Select | Surface structure | Brushed | Content of formaldehyde | E1 |
| Product type | 3-Layer | m² per carton | 3,06 | PCP content | NPD |
| Format | 5-1/2" plank | Boards per carton | 10 | Brinell Value (N/mm²) | 34 |
| Dimensions | 9/16 x 5-1/2 x 86-5/8 inch | Weight per carton (kg) | 25,5 | Shrinking and swelling | |
| Top layer thickness | 3,5 mm | m² per pallet | 128,52 | Breaking strength | NPD |
| Core material | Spruce / Spruce | Boxes per pallet | 42 | Thermal conductivity (W/(m²K)) | 0,131 |
| Connection | T/G | Weight per pallet (kg) | 1071 | Thermal resistance (m²K)/W | 0,107 |
| Floor heating | suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 91 |
| Treatment | Live Pure laquer | FSC claim | controlled sources | Antislip performance (DIN) | R11 |
| Appearance | Brown | Performance classification | Class 1 | Nobb.number | |
| Colour | Transparent | Density | >= 500kg/m ³ | EAN Code | 7035580206033 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.