

Oak smoked Nature Live Pure

10123763 / EE4733FD Article number Oak Wood Grading Nature Product type 3-layer parquet 14mm Plank 138 Format 14 x 139 x 2200 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection T/G Floor heating suitable Treatment Live Pure lacquer Appearance Dark floors Colour

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim

Biological durability Density

2
brushed
3,06
10
24
128,52
42
1008
EN 13489
controlled sources
Class 1
>= 500kg/m³

beveled 2V

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,129
Thermal resistance (m²*K)/W	0,109
Antislip performance (CE)	USRV 91
Antislip performance (DIN)	R11
Nobb.number	
EAN Code	703558020655

52



Wood is a product of nature - each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

