


Oak Elephant Grey

Product details / Technical properties

Article number	10125144	**Bevel**	beveled 2V	**Moisture content**	5-9%
Wood	Oak	**Number of slotted top layers**	1	**Fire classification (floating)**	Dfl-s1
Grading	Espressivo	**Surface structure**	brushed	**Fire classification (glued)**	Cfl-s1
Product type	3-layer parquet	**m² per carton**	2.76	**Content of formaldehyde**	E 1
Format	Plank Castle	**Boards per carton**	6	**PCP content**	NPD
Dimensions	14 x 209 x 2200 mm	**Weight per carton (kg)**	21.8	**Brinell Value (N/mm²)**	38
Top layer thickness	3.5 mm	**m² per pallet**	138	**Breaking strength**	NPD
Core material	Spruce / Spruce	**Boxes per pallet**	50	**Thermal conductivity (W/(m*K)**	0.129
Connection	5G® Click	**Weight per pallet (kg)**	1090.0	**Thermal resistance (m²*K)/W**	0.109
Floor heating	suitable	**EN Norm**	EN 13489	**Antislip performance (CE)**	USRV 91
Treatment	Live Pure™	**Wood origin**	controlled sources	**Antislip performance (DIN)**	R11
Appearance	dark	**Performance classification**	Class 1	**Nobb.number**	54522372
Colour	Elephant Grey	**Density**	>= 500kg/m³	**EAN Code**	7035580208433

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.