



# Oak White Vivo

## Product details / Technical properties

|                            |                         |                                     |                         |   |               |
|----------------------------|-------------------------|-------------------------------------|-------------------------|---|---------------|
| <b>Article number</b>      | 10125647 (EIG8V2FD)     | <b>Bevel</b>                        | beveled 2V              | <b>Moisture content</b>                       | 5-9%          |
| <b>Wood</b>                | Oak                     | <b>Number of slotted top layers</b> | 2                       | <b>Fire protection classification</b>         | Cfl-s1        |
| <b>Grading</b>             | Vivo                    | <b>Surface structure</b>            | unbrushed               | <b>Content of formaldehyde</b>                | E 1           |
| <b>Product type</b>        | 3-layer parquet         | <b>m<sup>2</sup> per carton</b>     | 3,04                    | <b>PCP content</b>                            | NPD           |
| <b>Format</b>              | 14mm Plank 138          | <b>Boards per carton</b>            | 10                      | <b>Brinell Value (N/mm<sup>2</sup>)</b>       | 38            |
| <b>Dimensions</b>          | 14 x 138 x 2200 mm      | <b>Weight per carton (kg)</b>       | 23,5                    | <b>Shrinking and swelling</b>                 |               |
| <b>Top layer thickness</b> | 3,5 mm                  | <b>m<sup>2</sup> per pallet</b>     | 127,68                  | <b>Breaking strength</b>                      | NPD           |
| <b>Core material</b>       | Spruce / Spruce         | <b>Boxes per pallet</b>             | 42                      | <b>Thermal conductivity (W/(m*K))</b>         | 0,129         |
| <b>Connection</b>          | 5G Click                | <b>Weight per pallet (kg)</b>       | 987                     | <b>Thermal resistance (m<sup>2</sup>*K)/W</b> | 0,109         |
| <b>Floor heating</b>       | suitable                | <b>EN Norm</b>                      | EN 13489                | <b>Antislip performance (CE)</b>              | USRV 33       |
| <b>Treatment</b>           | Live Matt lacquer white | <b>FSC claim</b>                    | controlled sources      | <b>Antislip performance (DIN)</b>             | R9            |
| <b>Appearance</b>          | Light floors            | <b>Biological durability</b>        | Class 1                 | <b>Nobb.number</b>                            | 56807463      |
| <b>Colour</b>              | White                   | <b>Density</b>                      | >= 500kg/m <sup>3</sup> | <b>EAN Code</b>                               | 7035580209058 |



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.