

Wood	Oak	Number of slotted top layers	2
Grading	Nature	Surface structure	unbrushed
Product type	2-layer parquet	m² per carton	2,24
Format	12.5mm Strip Traffic	Boards per carton	68
Dimensions	12.5 x 70 x 470 mm	Weight per carton (kg)	16,5
Top layer thickness	5,5 mm	m² per pallet	80,64
Core material	/ Spruce	Boxes per pallet	36
Connection	T/G	Weight per pallet (kg)	594
Floor heating	suitable	EN Norm	EN 13489

Bevel

without bevel	Moisture content	5-9%
2	Fire protection classification	Cfl-s1
unbrushed	Content of formaldehyde	E 1
2,24	PCP content	NPD
68	Brinell Value (N/mm²)	38
16,5	Shrinking and swelling	
80,64	Breaking strength	NPD
36	Thermal conductivity (W/(m*K)	0,14
594	Thermal resistance (m ² *K)/W	0,09
EN 13489	Antislip performance (CE)	USRV 33
controlled sources	Antislip performance (DIN)	R9
Class 1	Nobb.number	54931164
>= 500kg/m³	EAN Code	7035580211358



Live Matt lacquer

Golden floors

Transparent

10125680 (EIO2356D)

Article number

Treatment

Appearance

Colour



Density


Biological durability











Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

