



Oak Basic

Product details / Technical properties

Article number	10125681 (EIO2T56D)	Bevel	square edged	Moisture content	5-9%
Wood	Oak	Number of slotted top layers	2	Fire protection classification	Cfl-s1
Grading	Basic	Surface structure	unbrushed	Content of formaldehyde	E 1
Product type	2-layer parquet	m² per carton	2,24	PCP content	NPD
Format	12.5mm Strip Traffic	Boards per carton	68	Brinell Value (N/mm²)	38
Dimensions	12.5 x 70 x 470 mm	Weight per carton (kg)	16,5	Shrinking and swelling	
Top layer thickness	5,5 mm	m² per pallet	80,64	Breaking strength	NPD
Core material	/ Spruce	Boxes per pallet	36	Thermal conductivity (W/(m*K))	0,137
Connection	T/G	Weight per pallet (kg)	594	Thermal resistance (m²*K)/W	0,091
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Golden floors	Biological durability	Class 1	Nobb.number	56812541
Colour		Density	>= 500kg/m ³	EAN Code	7035580211365



Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.