

| Article number | 10126729 (EI1Y3KWD) | Bevel | beveled 4V | Moisture content | 5-9% |
|---------------------|----------------------|------------------------------|--------------------|--|---------------|
| Wood | Oak | Number of slotted top layers | 0 | Fire protection classification | Dfl-s1 |
| Grading | Nature | Surface structure | unbrushed | Content of formaldehyde | E 1 |
| Product type | 3-layer parquet | m² per carton | 1,65 | PCP content | NPD |
| Format | 15mm Plank Chaletino | Boards per carton | 2 | Brinell Value (N/mm²) | 38 |
| Dimensions | 15 x 300 x 2750 mm | Weight per carton (kg) | 14 | Shrinking and swelling | |
| Top layer thickness | 3,5 mm | m² per pallet | 64,35 | Breaking strength | NPD |
| Core material | Spruce / Spruce | Boxes per pallet | 39 | Thermal conductivity (W/(m*K) | 0,128 |
| Connection | T/G | Weight per pallet (kg) | 546 | Thermal resistance (m ² *K)/W | 0,117 |
| Floor heating | suitable | EN Norm | EN 13489 | Antislip performance (CE) | USRV 59 |
| Treatment | Live Natural oil | FSC claim | controlled sources | Antislip performance (DIN) | R10 |
| Appearance | Golden floors | Biological durability | Class 1 | Nobb.number | 55472786 |
| Colour | Transparent | Density | >= 500kg/m³ | EAN Code | 7035580210337 |











Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

