

Oak Transparent Traditional

10126731 (EI1Y4KWD) Article number Oak Wood Grading Traditional Product type 3-layer parquet 15mm Plank Chaletino Format 15 x 300 x 2750 mm Dimensions Top layer thickness 3,5 mm Core material Spruce / Spruce Connection T/G suitable Floor heating Live Natural oil Treatment Appearance Golden floors Colour Transparent

Bevel Number of slotted top layers Surface structure m² per carton Boards per carton Weight per carton (kg) m² per pallet Boxes per pallet Weight per pallet (kg) EN Norm FSC claim Biological durability Density

	beveled 4V
s	0
	sanded
	1,65
	2
	13,8
	64,35
	39
	538,2
	EN 13489
	controlled sources
	Class 1
	>= 500kg/m³

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,128
Thermal resistance (m ^{2*} K)/W	0,117
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	55472794
EAN Code	7035580210351





Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

