

beveled 4V

sanded

0,95

10

11

49

539

EN 13489

Class 1

>= 500kg/m³

controlled sources

46,55

0

Oak Transparent Adagio

Article number 10126790 (EIG82KND) Wood Oak Grading Adagio Product type 3-layer parquet 14mm Plank Herringbone Click 138, B-Plank Format Dimensions 14 x 138 x 690 mm Top layer thickness 3.5 mm Core material HDF / Spruce Connection 5G Click Floor heating suitable Treatment Live Natural oil Appearance Golden floors Colour Transparent

Bevel
Number of slotted top layers
Surface structure
m² per carton
Boards per carton
Weight per carton (kg)
m² per pallet
Boxes per pallet
Weight per pallet (kg)
EN Norm
FSC claim
Biological durability
Density

Product details / Technical properties

Moisture content	5-9%
Fire protection classification	Dfl-s1
Content of formaldehyde	E 1
PCP content	NPD
Brinell Value (N/mm²)	38
Shrinking and swelling	
Breaking strength	NPD
Thermal conductivity (W/(m*K)	0,143
Thermal resistance (m ^{2*} K)/W	0,098
Antislip performance (CE)	USRV 59
Antislip performance (DIN)	R10
Nobb.number	55493964
EAN Code	7035580210597







CE
06
Boen AS
Topdalsveien 406-408, 4658 Tveit, Norway
Parquet flooring according to EN 13489: 2017-12 and EN 14342-2013 9,5-23 mm total thickness; parquet for indoor use
DOP 4658; NB 0766
Dfl-sl; El, density $\approx 500 \text{kg/m}^3$ thermal conductivity ≈ 0.14 W/mK

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

